TA-CA2(14/38) is designed to be used with handheld or DSLR type cameras. It enables the ability to adapt 14.4V ENDURA V-Mount batteries and accessories to simultaneously supply DC power to handheld cameras and camera accessories. In addition, the TA-CA2(14/38) can be adapted to larger camera systems for flexible accessory mounting.

TA-CA214 / TA-CA238 Product Features:

- Various handheld and still cameras can be mounted.
- Ball joint clamp and cheese plate design enables fully customizable configurations.
- Can attach to mono/tripod adaptors.
- Compatible with all P-V series V-Mount plates
- When used with optional ENDURA battery system and accessories, long operation times are achieved.

Usage Examples:



Tripod Mount



Handheld - Compact



Handheld - Chest Support



Handheld - Under Support

Technical Specification

Material:

6061 Aluminum, black anodized.

Dimensions:

15.66 (L) x 3.24 (W) x 0.39 (H) inches Fully extended.

Weight:

1.25 approx.

Included Accessories:

 $1/4\mbox{-}20\mbox{"}$ (TA-CA214) or $3/8\mbox{-}16\mbox{"}$ (TA-CA238) camera mounting screws.

Please Note: TA-CA2(14/38) will not mount underneath all handheld cameras. The camera's 1/4-20" or 3/8-16" screw hole must be less than 4.5" or 3.7", respectively, from the rear of the camera.

Example:



IDX System Technology, Inc. 19001 Harborgate Way, Suite 105 Torrance, CA 90501

Telephone: (310) 328-2850 Fax: (310) 328-8202

